



SERIE 100

Silver / Black



CD 100 *

1'290.00

CD Player / Drive TEAC / BURR-BROWN 1796 / 40VA

Outputs / RCA / Optic / Coax / Remote / Option : Carte DAC DC200




IN 100 *

1'290.00

Amplifier / 2x 100W 8Ω / 660VA / 5 Line RCA / Bypass

2 Line Out RCA / Option : Remote / Carte Phono & Carte DAC DA200



Option *

P50 / Carte Phono MM

100.00

P100 / Carte Phono MM & MC

150.00

DC 200 / Optic / Coax / USB B


250.00

DA 200 / 2 Optic / 2 Coax / USB B / Bluetooth

395.00

Remote / Universal

60.00



SERIE MINI

Silver / Black



MS 120

1'400.00

Streamer / BURR-BROWN 1794 / Volume Fixe / Variable

2 Line RCA / 2 Optic / 2 Coax / 2 USB A / Bluetooth / RJ45 / Ethernet

Line Out RCA / Remote / App. Google Play & App Store



MD 100

750.00

CD Player / Drive TEAC / BURR-BROWN 5102 / 30VA

Outputs / RCA / Optic / Coax / Remote



MA 100

550.00

Power Amplifier / 2x 60W 8Ω / Bridge Mono 150W 8Ω / 170VA

1 Line RCA / 1 Line Out RCA



PH 100

450.00

Phono Box / MM / MC / Capacity : 100 μF

Price CHF : 8.1% VAT included

All other **Atoll Electronique** models are available, but only to order. Price and delivery times for each reference.
Subject to modifications, **Q4-2026**.

Atoll Electronique for Switzerland - <https://audiosynthese.ch> - info@audiosynthese.ch



ST 200

2'200.00

Streamer / BURR-BROWN 1792 / Volume Fixe / Variable
2 Line RCA / 2 Optic / 2 Coax / 2 USB A / Bluetooth / RJ45 / Ethernet
Line Out RCA / Remote / App. Google Play & App Store



CD 200 *

1'890.00

CD Player / Drive TEAC / BURR-BROWN 1792 / 60VA
Outputs / RCA / Optic / Coax / Remote / Option : Carte DAC DC200



DR 200

1'500.00

Transport / Drive TEAC / 30VA / LVDS
Outputs / Optic / Coax / AES/EBU / Remote



SDA 200

3'200.00

Streamer / Amplifier / 2x 120W 8Ω / 660VA / BURR-BROWN 1792
2 Line RCA / 2 Optic / 2 Coax / 2 USB A / Bluetooth / RJ45 / Ethernet
Line Out RCA / Remote / App. Google Play & App Store



IN 200 *

1'890.00

Amplifier / 2x 120W 8Ω / 660VA / 5 Line RCA / Bypass
2 Line Out RCA / Remote / Option : Carte Phono & Carte DAC DA200




PH 200

1'250.00

Phono Box / MM / MC HI / MC LO / Capacity : 100 / 220 / 320 μF

Option *




P50 / Carte Phono MM

P100 / Carte Phono MM & MC

DC 200 / Optic / Coax / USB B

DA 200 / 2 Optic / 2 Coax / USB B / Bluetooth



100.00

150.00

250.00

395.00

SERIE 300

Silver / Black



ST 300

3'000.00

Streamer / 2x BURR-BROWN 1792 / Volume Fixe / Variable

2 Line RCA / 2 Optic / 2 Coax / 2 USB A / Bluetooth / RJ45 / Ethernet

2 Line Out / RCA / XLR / Remote / App. Google Play & App Store



SDA 300

4'150.00

Streamer / Amplifier / 2x 150W 8Ω / 880VA / BURR-BROWN 1792

2 Line RCA / 2 Optic / 2 Coax / 2 USB A / Bluetooth / RJ45 / Ethernet

Line Out RCA / Remote / App. Google Play & App Store



IN 300 *

2'800.00

Amplifier / 2x 150W 8Ω / 880VA / 86'150 μF

5 Line RCA / XLR / Bypass / 2 Line Out RCA / Remote

Option : Carte Phono & Carte DAC DA200



PR 300 *

2'100.00

Preamplifier / 89'000 μF / 5 Line RCA / Bypass / XLR

2 Line Out RCA / Line Out XLR / Trigger 12v / Remote

Option : Carte Phono & Carte DAC DA200



AM 300

2'450.00

Power Amplifier Double Mono / 2x 150W 8Ω / Bridge Mono 500W 8Ω

880VA / 1 Line RCA / 2 Line Out / RCA / XLR

SERIE 400

Price CHF : 8.1% VAT included



IN 400 Evolution *

5'500.00

Amplifier / 2x 160W 8Ω / 2x 3000W 4Ω / 1'050VA / 96'680 μF

5 Line RCA / 2 Line XLR / Bypass / 2 Line Out RCA / Remote

Option : Carte Phono & Carte DAC DA200



CD 400 Evolution

5'700.00

Top Loader / Double mono / 2x 10VA audio / 30VA / 1,6VA logic / 48'000 μF

2x BURR-BROWN 1792A / Digital In : USB-B - Coaxial - Optic

Digital Out : AES/EBU - Coaxial - Optic / Analog Out : RCA / XLR / Remote



IN800 *EVOLUTION*

INTEGRATED AMPLIFIER – PREAMPLIFIER

Ultra-high-end integrated amplifier

- 12 mm brushed, bead-blasted, and anodized aluminum front panel with high-precision engraving.
- Machined aluminum heatsink and knobs.
- 2 mm steel chassis.
- Toroidal transformers: 1200 VA (audio) mechanically decoupled + 1.6 VA (control logic) + 25 VA (digital control) + 7 VA (analog control).
- High-quality shielded MKP coupling capacitors.
- Integrated dual mono structure:
 - Separate windings for left and right channels.
 - High-precision MUSE attenuators: One per channel with switched resistors.
- Bipolar transistor input stages.
- Bipolar transistor and LED current sources for perfect stability.
- Darlington transistor driver stages.
- Audio stages with a perfectly symmetrical structure and very low negative feedback.
- MOS-FET transistor power stages rigorously matched (16 per channel).
- Internal speakers output wiring using Absolue Créations cable.
- Active thermal protection.
- High-resolution TFT display (480x1280) with adjustable brightness.
- Precise balance control with memory function.
- Input renaming capability.
- Selectable standby mode: Low power or warm-up.
- DAC and MM or MC phono boards available as options.
- Aluminum remote control included as standard.





Rear view of the IN800 EVO equipped with the DA800 and P800 boards.

CONNECTIVITY

- 2 XLR Inputs
- 3 RCA LINE Inputs + 1 RCA TAPE Input/Output
 - BY-PASS configuration: 1 RCA Input and 1 XLR Input
- 12 V Trigger Input
- 12 V Trigger Output
- XLR PRE-OUT Output
- RCA PRE-OUT Output
- Compatible with the DA800 digital board and the P800 PHONO board

TECHNICAL DATA

CHF 12'000.00

Power:	2×350 Wrms / 8Ω 2×550 Wrms / 4Ω
Total of capacitors:	128 000 µF
Bandwidth (–3 dB):	5 Hz – 100 kHz
Rising time:	2 µs
Input impedance:	220 kΩ
Sensitivity:	400 mV
Signal-to-noise ratio:	100 dB
Distortion at 1 kHz:	0,05 %
Standby power consumption (low power):	< 0,5 W
Dimensions:	443×440×147 mm
Weight:	27 Kg

Data is subject to change.

DA800 :

DAC board for IN800



CONNECTIVITY

- 1 AES/EBU input (44.1 kHz to 192 kHz)
- 2 Coaxial inputs (44.1 kHz to 192 kHz)
- 2 Optical inputs (44.1 kHz to 192 kHz)
- 1 USB input (PCM from 44.1 kHz to 768 kHz and DSD 64 to DSD 256)
- 1 Bluetooth 5.0 input

TECHNICAL DATA

CHF 1'200.00

Dual AK4497S converters:

- Dynamic range: 133 dB
- Signal-to-noise ratio: 133 dB
- Decoded formats: up to 32-bit / 768 kHz

XMOS USB converter:

- Asynchronous operation
- Custom ATOLL firmware
- PCM up to 32-bit / 768 kHz and DSD64 to DSD256

BM83 Bluetooth module:

- Bluetooth 5.0: 16-bit and 24-bit at 44.1 kHz and 48 kHz
- I2S output connected to AK4497S converters
- Screw-on external antenna

P800

Phono board for IN800



SPECIFICATIONS

Configurable for MM and MC (low, medium, and high gain)
Two high-performance MC transformers (Lundahl)
Class A biased discrete component stages

TECHNICAL DATA

CHF 900.00

Input impedance: 47 k Ω
Signal-to-noise ratio: 100 dB
Crosstalk at 1 kHz: < -86 dB
Frequency response
(20 Hz - 20 kHz): < 0.1 dB
THD at 1 kHz: 0.005%
MM gain: 41 dB (*)
High-output MC gain: 59 dB (*)
Medium-output MC gain: 65 dB (*)
Low-output MC gain: 71 dB (*)

(*) depending on card configuration